

# Dynapac F1200CS

## Compact pavers



### Technical data

 <b>Masses</b>	
Paver weight (incl. standard screed)	13,000 lbs
 <b>Dimensions</b>	
Basic width	3.9 ft
Working width, max.	10.2 ft
Working width, hydraulic extendable	7.9 ft
Working width, minimum (Cut Off Shoe)	0.98 ft
Front ramp angle	15,5°
 <b>Capacity</b>	
Paving thickness (max/min)	7.9 /-5.9 in
Theoretical placement capacity	300 t/h
 <b>Material hopper</b>	
Capacity	81 cu. ft. (11,000 lbs)
Dumping height, center	22 in
Hopper width, internal	111 in
 <b>Propulsion</b>	
Paving speed	up to 90 ft/min
Transport speed	180 fpm
 <b>Operation stations</b>	
Control consoles	Slidable left/right
Platform	Extendable platform

 <b>Engine</b>	
Manufacturer/Model	Deutz TD2.9 L4
Emissions according to	US T4f
Rated power	66 hp @ 2,200 rpm
Electrical system	2 x 24V, 72 Ah
Fuel tank capacity	22 gal

 <b>Undercarriage</b>	
Crawler length	54.7 in
Crawler width	8.1 in
Final drive	Direct drive over transmissions

 <b>Conveyor</b>	
Conveyor type	Splitted conveyor drive with center cover
Conveyor width	25.6 in
Conveyor control	Automatic with limit switches

 <b>Auger</b>	
Auger diameter	12.6 in
Auger control	Automatic with ultrasonic sensor
Auger height adjustment	Infinitely variable by 6 in

Find us locally at [www.dynapac.us](http://www.dynapac.us)



We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.

# Dynapac F1200CS

## Compact pavers



### Technical data



Dimensions	
A. Axle track	54.7 in
B1. Width, max.	111.4 in
B2. Width, standard	3.9 ft
B3. Width, center of tracks	37.0 in
C1. Track width	8.1 in
H2. Height, transport	74.8 in
H3. Height	19.3 in
L1. Length, total	14.3 ft
L2. Length, transport	3880 mm
L3. Length, hopper	51.6 in

Standard equipment	
2 front & 2 rear lights, Conventional electrics, Conveyor reversible (splitted), Dashboard with toggle switches, Eco Mode, Extendable steps operator platform, Hopper hydraulic separate control, Mechanical auger height adjustm., Mechanical conveyor limit switches, Ultrasonic sensors auger, back up alarm, emulsion spray equipment, pump, foldable material guide plates, LED lights	

Optional equipment	
Cut off shoes (9.8 in or 13.8 in), Emulsion spray equipment (Gloria), hose dispenser, Fire extinguisher, First aid kit, Light for auger compartment, Material laying kit (left or right), Panolin bio hydraulic oil, Remote steering device, Rotating flashing beacon, Side shield easy adjust, Special painting, Working widths	

Suitable screeds					
Model	Basic width	Working width, hydraulic extendable	Working width, max.	Compacting elements	Heating system
Dynapac V240TVE	3.94 ft	7.87 ft	10.17 ft	Vertical tamper /vibration	Electrical
Dynapac V240TV	3.94 ft	7.87 ft	10.17 ft	Vertical tamper /vibration	Propane (LPG)

Find us locally at [www.dynapac.us](http://www.dynapac.us)

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.