Dynapac MF2500CM



Mobile feeders



Technical data

	Masses	
	Transport mass	21 t
RAMMARKA MARKA	Dimensions	
	Front ramp angle	10°
	Material hopper	
	Capacity	6.0 m ³
	Dumping height, center	525 mm
©	Traction	
	Operating speed, max	25m/min
	Transport speed, max	4 km/h

Engine	
Manufacturer/Model	Cummins QSB 6.7-C220
Rated power, SAE J1995	164 kW (220 hp) @ 2200 rpm
Electrical system	24 V
Emissions according to	Stage 3A /Tier 3

Engine	
Manufacturer/Model	Cummins QSB 6.7-C225
Rated power, SAE J1995	168 kW (225 hp) @ 2200 rpm
Electrical system	24V
Emissions according to	Stage 4 /Tier 4f


Conveyor	
Conveyor type	Rubber belt on two chains, mounted with metal stiffeners
Conveyor speed	Contantly variable
Conveyor width	1.20 m
Feeding height (max/min)	3.0 m /2.1 m
Feed capacity	4000 t/h


Dynapac MF2500CM



Mobile feeders

Technical data





Dimensions	
A. Axle track	3.90 m
B1. Width, max.	3.35 m
B2. Width, standard	2.55 m
B3. Width, wheel track	2.09 m
C1. Track width	0.57 m
H1. Height, max.	4 m
H2. Height, transport	3.10 m
H3. Height	0.57 m
H4. Height, max.	5 m
H5. Feeding height, max.	3.0 m
H6. Feeding height, min.	2.1 m
L1. Length	10.30 m
L3. Length, hopper	2.29 m